

Sub B1
Cond A1

2. A camera, comprising:
a display unit to display a camera setting and/or a control state;
a mode selection unit to select at least one mode setting position at which a function related to a photographing operation can be selected and set;
a selection/setting operation unit to select and set the function;
a reset operation unit to reset the function to a specific initial state; and
a reset control unit to implement the reset control unit to reset display on the display unit when the reset operation unit has been operated, wherein
a release operation is enabled when the mode selection unit is set in, at least, one first mode setting in which a first function related to a photographing operation can be selected and set and the release operation is prohibited when the mode selection unit is set in, at least, one second mode setting in which a second function other than the first function can be selected and set.

Sub A1
C1

4. The camera of claim 1, wherein the reset control unit indicates a reset by momentarily turning off the display unit.

5. The camera of claim 1, wherein
the reset operating unit is provided with two operating members; and
the reset control unit determines that the reset operation unit has been operated when the two operating members have been continuously operated together over a period equal to or greater than a predetermined length of time.

6. A camera reset device, comprising:
a mode selection unit to select, at least, one mode setting state in which a function related to a photographing operation can be selected and set;
a selection/setting operation unit to select and set the function;
a reset operation unit to reset the function to a specific initial state; and
a reset control unit to reset only a function which can be selected and set in the mode setting state selected by the mode selection unit when the reset operation unit has been operated, wherein
a release operation is enabled when the mode selection unit is set in, at least, one first mode setting in which a first function related to a photographing operation can be

C' Cond #2
selected and set and the release operation is prohibited when the mode selection unit is set in, at least, one second mode setting in which a second function other than the first function can be selected and set.

Sub C2
8. The camera reset device of claim 7, wherein the mode selection unit is capable of selecting, at least, one setting among photographing condition settings in which a photographing condition of a photographing operation started by issuing a photographing start instruction in the camera can be set, a custom setting, in which value settings for a plurality of functions can be set independently of one another and a film sensitivity setting in which the film sensitivity can be set, and details that can be reset by the reset control unit when the reset operation unit has been operated in a given setting selected by the mode setting unit only include a numerical value or a state that can be set in the setting.

Please ADD new claim 9, as follows:

App Sub #3
9. A camera resetting method, comprising;
displaying a camera setting and/or a control state;
selecting at least one mode setting position at which a function related to a photographing operation can be selected and set;
selecting and setting the function;
resetting the function to a specific initial state; and
displaying a reset by achieving a no-display state of a display over a specific short period of time upon the resetting of the function.
